

BEG 2000 B



This dispersion system can continuously generate low mass flows, e.g., 100 g/h, with optimal dosing constancy and control with automatic mass flow monitoring. Mass flow setting of approx. 100 g/h – 6 kg/h based on SAE fine, A2 dust.

BENEFITS

- Excellent short-term and long-term dosing constancy
- Easy to operate
- Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1,500 cm³)
- Automatic mass flow control with the BEG 2000
- Robust design, proven in industrial applications
- Reliable function
- Reduces your operating expenses
- Low maintenance

APPLICATIONS

- Loading test of
 - engine filters as per ISO 5011
 - Hot gas filters
 - Bag filters
 - Air filters
 - Cyclones
- Engine crash tests
- Chemical and pharmaceutical industry
- Cement industry

DATASHEET

Particle size range	0.1 – 200 μm	Maximum particle number concentration	Ca. 10^7 particles/ cm^3
Volume flow	80 – 165 Nl/min	Mass flow (particles)	Typ A: 8 g – 550 g/h (bezogen auf SAE Fine, A2 Staub), Typ B: 100 – 6.000 g/h (bezogen auf SAE Fine, A2 Staub), Typ C: 350 – 7.300 g/h (bezogen auf SAE Fine, A2 Staub)
Filling quantity	500 g	Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks	Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar	Carrier/dispersion gas	Random (generally air)
Compressed connection	air Quick coupling	Aerosol outlet connection	Type A: $\varnothing_{\text{inside}} = 6.4$ mm, $\varnothing_{\text{outside}} = 10$ mm Type B: $\varnothing_{\text{inside}} = 8$ mm, $\varnothing_{\text{outside}} = 12$ mm Type C: $\varnothing_{\text{inside}} = 6.2$ mm, $\varnothing_{\text{outside}} = 10$ mm
Reservoir volume	1,500 cm^3		