

BEG 2000 C



This dispersion system is able to generate high mass flows continuously, e.g., 7.3 kg/h, with optimal dosing constancy and control with automatic mass flow monitoring. Mass flow setting of approx. 350 g/h – 7.3 kg/h based on SAE fine, A2 dust.

OPERATION PRINCIPLE

BENEFITS

- Excellent short-term and long-term dosing constancy
- Easy to operate
- Quick and easy to clean
- Remote control or computer-controlled
- Pulse mode
- Easy to fill while in operation
- Large reservoir (1,500 cm³)
- Automatic mass flow control with the BEG 2000
- Robust design, proven in industrial applications
- Reliable function
- Reduces your operating expenses
- Low maintenance

DATASHEET

Particle size range	0.1 – 200 μm
Maximum particle number concentration	Ca. 10^7 particles/cm ³
Volume flow	80 – 165 Nl/min
Mass flow (particles)	Type C: 350 – 7,300 g/h (with reference to SAE Fine, A2 dust)
Filling quantity	500 g
Power supply	115 – 230 V, 50/60 Hz
Particle material	Non-cohesive powders and bulks
Dosing time	Several hours nonstop
Pre-pressure	4 – 8 bar
Carrier/dispersion gas	Random (generally air)
Compressed air connection	Quick coupling
Aerosol outlet connection	Type A: $\varnothing_{\text{inside}} = 6.4 \text{ mm}$, $\varnothing_{\text{outside}} = 10 \text{ mm}$ Type B: $\varnothing_{\text{inside}} = 8 \text{ mm}$, $\varnothing_{\text{outside}} = 12 \text{ mm}$ Type C: $\varnothing_{\text{inside}} = 6.2 \text{ mm}$, $\varnothing_{\text{outside}} = 10 \text{ mm}$
Reservoir volume	1,500 cm ³

APPLICATIONS

- Loading test of
 - engine filters as per ISO 5011
 - Hot gas filters
 - Bag filters
 - Air filters
 - Cyclones
- Engine crash tests
- Chemical and pharmaceutical industry
- Cement industry



Mehr Informationen:
<https://www.palas.de/product/beg2000c>