DEMC 2000





The DEMC size classifier (as defined in ISO 15900) selects aerosol particles based on their electrical mobility and directs them to the outlet. It is also often referred to as a DMA.

The size classifier is suitable in combination with condensation particle counters from the Palas UF-CPC, ENVI-CPC series or electrometers (Charme®) for measuring the number concentrations of different aerosols in scientific and regulatory environments. Alternatively, columns and particle counters from other manufacturers can also be integrated.

BENEFITS

- The user is able to select any size within the defined size range.
- The DEMC can be connected to many counters to form an SMPS.
- Continuous and fast-scanning principle of measurement
- Graphic display of measurement values
- Intuitive operation using 7" touchscreen and GUI
- Integrated data logger
- Low maintenance
- Reliable function
- Reduces your operating expenses

APPLICATIONS

- Calibration of condensation particle counters (CPC)
- Monodisperse particle source
- System component of an SMPS

MODEL VARIATIONS



DEMC 2000 X Differential electrical mobility classifier from 8 – 1400 nm with integrated X-ray ionization

https://www.palas.de/product/demc2000x

PALAS

DATASHEET

Volume flow (sheath air)	2.5 – 14 l/min	Size channels	Max. 256 (128/decade)
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)	Data logger storage	4 GB
Software	PDAnalyze	Classifying range (si- ze)	4 – 1,489 nm
Installation conditions	+5 – +40 °C (control unit)	Impactor	Nozzle for 3 different cut-offs
Adjustment range (vol- tage)	1 – 10,000 V	Data Management	Prepared for connection to the Palas Cloud MyAtmo- sphere ("MyAtmosphere- ready"); internet access and separate registration requi- red.MyAtmosphere terms and conditions of use apply.