

MFP 3000 C



Version MFP 3000 C is specially tailored to the requirements of the DIN 71460 and 'ISO 11155-1 Road vehicle interior filters measurement procedures.

BENEFITS

- Virtually simultaneous particle measurement in the raw gas and clean gas
- Particle size measurements from 0.2 – 40 μm
- Measurement of $C_{n \text{ max}} = 10^5$ particles/ cm^3 without dilution
- Internationally comparable measurement results
- Widespread distribution of the measurement system
- High reproducibility of the testing method
- Easy use of different test aerosols, e.g. SAE Fine and Coarse, NaCl/KCl, DEHS
- Highest raw gas concentrations of up to $> 100 \text{ mg}/\text{m}^3$ (ISO Fine) or $> 500 \text{ mg}/\text{m}^3$ (ISO Coarse) with measurement of the fraction separation efficiency for burden tests
- Flexible filter test software FTControl
- Sequence programs for pressure loss measurements, measurements of fraction separation efficiency and burden measurements
- Easy to operate, even untrained personnel can be instructed quickly in the use of the equipment
- Short set-up times
- Cleaning and calibration can be performed autonomously by the customer
- Easy use of the measurement technology components – even in other applications
- Mobile setup, easy to move on castors

APPLICATIONS

- Testing of filter media and small filter elements in product development and during production monitoring.
- Testing option based on ISO 11155-1 / DIN 71460-1 (cabin air filters).

DATASHEET

Aerosols	Dusts (e.g., SAE dusts), salts (e.g., NaCl, KCl), liquid aerosols (e.g., DEHS)	Test area of the medium	100 cm ²
Measurement (size)	range 0.2 – 40 μm	Measurement (mass)	range Up to 1,000 mg/m ³ (depending on the version)
Volume flow	1 – 35 m ³ /h - suction mode	Differential pressure measurement	0 – 1,200 Pa selectable, 0 – 2,500 Pa selectable, 0 – 5,000 Pa selectable
Inflow velocity	5 cm/s – 1 m/s (others on request)	Compressed air supply	6 – 8 bar
Dimensions	2.500 • 680 • 1.550 mm (H • B • T)		