



Depending on the aerosol composition to be measured, i.e., the carrier gas component and the particle material, pressure changes in the carrier gas can significantly influence the particle size distribution, e.g., due to condensation or evaporation.

For this reason, the [welas[®] aerosol sensors welas[®] 2070 P, 2100 P, 2200 P, 2300 P, and welas[®] 2500 P¹](#) are equipped with a pressure-tight cuvette to ensure isobaric and isothermal sampling into the sensor's measurement volume.

The Promo[®]system is usually calibrated for the operating volume flow. As the operating volume flow changes with pressure, it is advantageous for the user if automatic volume flow regulation for the sampling volume flow is provided for in the device.

In the Promo[®]3000 P, the pressure of the carrier gas is measured, and the required operating volume flow is automatically set to 5 l/min.

Includes:

- Mass flow controller for volume flow regulation
- Absolute pressure capsule
- Filter unit to protect the flow rate control

OPERATION PRINCIPLE

¹welas[®] aerosol sensors welas[®] 2070 P, 2100 P, 2200 P, 2300 P and welas[®] 2500 P: <http://www.palas.de//product/aerosolsensors>

BENEFITS

- Measuring range of 0.2 to 100 μm (4 measuring ranges selectable in one device)
- Up to four measuring ranges in only one device:
 - 0,2 μm – 10 μm
 - 0,3 μm – 17 μm
 - 0,6 μm – 40 μm
 - 2 μm – 100 μm (additionally for sensors 2300 and 2500)
- Up to 128 size channels per measuring range
- Concentration range of 1 particle/ cm^3 to 10^6 particles/ cm^3
- Calibration curves for different refractive indices
- Very high and reproducible counting efficiency rate starting at 0.2 μm
- Pressure-resistant up to 10 bar (optional)

- Optical fibre technology
- Simple operation with a large touch display
- Calibration, cleaning and lamp replacement can all be performed independently by the customer
- External control by RS 232 or Ethernet
- With analysis software PDAnalyze
- Optional: Software PDControl for operation as welas® digital available
- Low maintenance
- Reliable function
- Reduces your operating expenses

DATASHEET

Measuring principle	Optical light-scattering
Measurement range (number C_N)	$< 1 \cdot 10^6$ Partikel/cm ³
Measurement range (size)	0.2 – 10 μm , 0.3 – 17 μm , 0.6 – 40 μm , 2 – 100 μm
Volume flow	5 l/min
Size channels	Max. 128 (64/decade)
Time resolution	1 s
Interfaces	USB, Ethernet (LAN), Wi-Fi, RS-232/485
User interface	Touchscreen, 800 • 480 pixel, 7" (17.78 cm)
Data logger storage	4 GB Compact Flash
Software	PDControl, FTControl, PDAnalyze
Thermodynamic conditions	+10 – +40 °C, -100 – 50 mbar
Data acquisition	Digital, 20 MHz processor, 256 raw data channels
Light source	Xenon arc lamp 35 W
Housing	Table housing, optional: with mounting brackets for rack-mounting
Support options	Direct remote access, Palas webserver service
Operating system	Windows embedded
Power supply	115 – 230 V, 50/60 Hz
Power consumption	100 W
Installation conditions	+5 – +40 °C (control unit)
Dimensions	185 • 450 • 315 mm (H • W • D) (19")
Weight	Control unit: approx. 8 kg, sensor: approx. 2.8 kg

APPLICATIONS

- Emission monitoring of installations
- Control of grinding and classification processes
- Monitoring of production processes in the food, pharmaceuticals and chemicals industries
- Testing of complete filters, inertial and wet separators or electrostatic precipitators



Mehr Informationen:
<https://www.palas.de/product/promo3000p>